



Marley

GOODWAY
CTV

Clean, Efficient Towers With No Downtime

TOWERVAC™ REMOVES POLLUTANTS, SAVES ENERGY AND CONTROLS CHEMICAL & WATER WASTE.



PATENTED



CTV-1501 – Efficiency with No Hassles

Safely remove cooling tower bacteria without having to drain or shut down the system. This award winning product features an adjustable flow control that allows you to vacuum at a recovery rate of up to 60 GPM. Easily remove slime, algae, mud and other contaminants from the sides and floor of any cooling tower basin or sump. Stop dirty cooling tower water from fouling chillers, robing efficiency and increasing energy costs.



FEATURES

- > Stainless steel construction
- > Heavy-duty motor removes up to 60 gallons of water and debris per minute
- > Semi-automatic pump primer
- > Adjustable flow control
- > In-line sediment filter
- > Quick connect hoses and tools
- > Easy storage of accessories

Specifications	CTV-1501
Motor Power	1 1/2 HP
Input Power	Standard: 15 amps, 115 V, 60 Hz AC Optional: 15 amps, 115 V, 50 Hz; 7.5 amps, 230 V, 60 Hz; or 7.5 amps, 230 V, 50 Hz
Power Supply Cord	21', 14-3 GFCI
Static Water Lift	25'
Water Displacement	Variable, 0-60 GPM
Filtration	3/16" sediment capture
Pump	Centrifugal
Dimensions	35" high x 22" wide x 21" deep
Weight	125 lbs

CTV-1501-60

TowerVac Cooling Tower Vacuum, including 15' inlet and 25' outlet vinyl crush proof hoses, 48" wand, 6" gulper tool and storage bag

\$3,495.00

Accessories:

CTV-EH-25 25' vinyl crush proof extension hose

6225A 36" extension tube

6225-4A 6" gulper tool

6229A 20" floor brush

6225-3A 12" paddle tool

6228A-HOSE-ASSY 18" bulk pickup tool on hose extension

6230A 6" utility brush



CTV-KIT-1501 Cooling Tower Vacuum Accessory Kit 1 1/2": 25' vinyl crush proof extension hose, 36" extension tube, 20" floor brush, 12" paddle tool, 18" bulk pickup tool on hose extension and 6" utility brush

Note: Call for additional accessories.



A Clean Start For Your Cooling Tower

CLEAN, FILTER AND REUSE COOLING TOWER WASTE WATER

CTV-F2 – Ideal Vacuum Companion

High-flow capability and small-micron filtration make this the perfect unit for filtering cooling tower wastewater and returning clean, reusable water to your tower basin. When used in conjunction with the CTV-1501 Cooling Tower Vacuum, this powerful cleaning duo provides you with an advanced, integrated system that is designed specifically to restore optimal operating conditions to cooling towers. Twin filter cartridges clean tower water down to 5 microns for better performance. The filters are easy to clean and reuse. A clean water discharge rate of up to 50 GPM means it can handle any heavy-duty tower-cleaning job you encounter.

CTV-F2

Cooling Tower Vacuum Filtration System, including two 5 micron media filters, 25' connection hose, 25' outlet hose and mobile dolly

Note: Call for additional accessories.

Replacement Filters:

9703 Replacement Filter

9703-6 Replacement filters (package of six)



FEATURES

- > Reusable filters
- > Quick lock lids
- > Quick connect hoses and tools

Specifications	CTV-F2
Input Water Pressure	Maximum 30 PSI at 50 GPM
Filters	Two reusable synthetic, 40 square foot, 5 micron media
Dimensions	38" high x 20" wide x 20" deep
Weight	70 lbs net dry



You Wouldn't Shower With Just Water

DON'T SKIMP ON SUDS WHEN IT COMES TO CLEANING YOUR COOLING TOWER FILL.



TFC-100 – Penetrating Cleaning Power

The expanding foam action of the TFC-100 is one of the most powerful weapons you can use against the dirt and biological build up on cooling towers. Although it will make deposits disappear right before your eyes, the secret behind this unit's penetrating cleaning power is not magic. It's the integrated continuous-duty air compressor that enhances the expansion of Goodway's environmentally sensitive cleaning solution, to loosen and rinse away deposits from the tightest crevices. The unit's powerful spray gun and custom extension wands and nozzles allow you to penetrate all the hard-to-reach areas of your cooling tower. This enables you to apply 100% Goodway cleaning solution, a combination of solution and water, or just water for powerful rinsing action.



TowerShine:

TowerShine is an environmentally friendly, biodegradable, expanding foam detergent specifically formulated for use with the TowerWash.

TOWERSHINE-5 Cooling Tower Fill Cleaning Solution, 5 gallon bucket

TFC-100

TowerWash Cooling Tower Foamer, including 35' chemical resistant hose, spray gun, 30" foaming wand with quick connect, 30" foaming wand with 90° elbow and quick connect, 30" extension wand with quick connect, fan nozzle, rinsing attachment, and a 5 gallon bucket of TowerShine

Note: Call for additional accessories.

FOAM-CLEAR-01 Foam Clear defoaming solution, 1 gallon bottle

FEATURES

- > Integrated continuous duty air compressor for enhanced foam production
- > Custom wand extensions and nozzles
- > Heavy-duty, chemical resistant components and dolly
- > Platform to hold one standard 5 gallon chemical container
- > Water hose connection to dilute cleaning solution or provide a clean water rinse
- > Hose, wand and tool holders

Specifi cations	TFC-100
Compressor Output	60 PSI at 1 CFM
Input Power	Standard: 5 amps, 115 V, 50/60 Hz AC Optional: 2.5 amps, 230 V, 50/60 Hz
Power Supply Cord	21', 14-3 w/ GFCI
Output Foaming Volume	20 GPM
Output Water Pressure	Same as supplied
Output Water Flow	1.6 GPM
Pump	Positive displacement diaphragm
Dimensions	48" high x 19" wide x 26" deep

