

Up to 4.000" O.D. (101.6 mm)

The H&S Track Saw 400 is a proven, patented design that makes cutting waterwall panels and removing membranes fast, safe and easy.

The saw and the membrane attachment are mounted on a carriage which rides on a special track for smooth, easy operation. Simply slide the saw to the cut point and plunge cut through the entire panel up to 4.000" (101.6mm) O.D.

The track sections are supplied in 6.0' (1.8 m) lengths. They are easily assembled into greater lengths by attaching them with a single bolt. Evenly spaced weld tabs with cut line locators make a straight, rigid base for accurate sawing.



Weld tabs have cut line indicators to speed and ease the setup process.



- **Powerful, Reliable Pneumatic Power**
- **Strong, Lightweight Track Sections**
- **Cuts Panels And Membranes With Only One Adapter**
- **Safe, Efficient Cutting**
- **U.S. Patent Protected Numbers 7653997 and 7673549**



Specifications*

Working Range	Up to 4.000" (101.6 mm)
Motor/Carriage Weight.....	32.0 lbs. (14.5 Kg.)
Air Volume Requirements	85 CFM(2.4 m3/min.)
Air Pressure Required	90 PSI (6.1 Bar)
RPM.....	3,300
Track length	6.0' (1.8 m)
Track Weight w/3 weld tabs	15.0 lbs. (6.8 kg.)
Pneumatic Motor	7.0 H.P. (5.3 kW)
Overhead Clearance	1.500"(38.1 mm)

*Specifications are subject to change without notice.

P.O. Box 393
 Wadsworth, OH 44282, U.S.A.
 Tel: +1-330-336-4550
 Fax: +1-330-336-9159
 email: info@hstool.com

Web Sites: hstool.com & multiprep.com